

No	Model Name	(1)	(2)	(3)							(4)	(5)	(6)							(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)
		Rated heat output	Seasonal efficiency	Declared capacity for heating/Average climate							Bivalent temperature	Degradation co-efficient	Declared coefficient of performance for heating/Average Climate							For air-to-water heat pumps: Operation limit temperature TOL	Heating water operating limit temperature WTOL	Electric power input				Capacity control	Sound power level	Rated air flow
				Pdh									Tbiv	Cdh	COPd							off mode Poff	standby mode Psb	thermostat-off mode Pto	crankcase heater mode Pck			
		kW	%	kW	kW	kW	kW	kW	kW	kW	°C															dBA	m³/h	
1	RUAGP421HL8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
2	RUAGP421HLN8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
3	RUAGP421HLR8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
4	RUAGP421H1N8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
5	RUAGP421H18TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
6	RUAGP421H1N8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
7	RUAGP421H28TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
8	RUAGP421H2N8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
9	RUAGP421H2R8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
10	RUAGP421H2NR8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
11	RUAGP421H38TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
12	RUAGP421H3N8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
13	RUAGP421H3R8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
14	RUAGP421H3NR8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
15	RUAGP421H58TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
16	RUAGP421H5N8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
17	RUAGP421H5R8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
18	RUAGP421H5NR8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
19	RUAGP421H78TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
20	RUAGP421H7N8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
21	RUAGP421H7R8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
22	RUAGP421H7NR8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
23	RUAGP421FL8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
24	RUAGP421FLN8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
25	RUAGP421FLR8TR	150	168	103	63.2	40.9	17.5	117	117	-	-10	0.9	3.38	4.3	4.73	5.23	3.07	3.07	-10	55	0.239	-	1.832	0.239	variable	83.8	73,800	
26</td																												