

No	Model Name	(1)	(2)	(3)							(4)	(5)	(6)						(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)
		Rated heat output	Seasonal efficiency	Declared capacity for heating/Average climate							Bivalent temperature	Degradation coefficient	Declared coefficient of performance for heating/Average Climate						For air-to-water heat pumps: Operation limit temperature TOL	Heating water operating limit temperature WTOL	Electric power input				Capacity control	Sound power level	Rated air flow
		Prated	ηs	Pdh							Tbiv	Cdh	COPd						TOL	WTOL	off mode	standby mode	thermostat-off mode	crankcase heater mode		Lwa	m³/h
				Tj=-7°C	Tj=2°C	Tj=7°C	Tj=12°C	Tj=biv	Tj=OL	Tj=-15			Tj=-7°C	Tj=2°C	Tj=7°C	Tj=12°C	Tj=biv	Tj=OL			Poff	Psb	Pto	Pck			
kW		%	kW							°C								°C	°C	kW	kW	kW	kW		dBa		
45	RUAGP511HL8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
46	RUAGP511HLN8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
47	RUAGP511HLR8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
48	RUAGP511HLNR8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
49	RUAGP511H18E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
50	RUAGP511H1N8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
51	RUAGP511H28E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
52	RUAGP511H2N8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
53	RUAGP511H2R8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
54	RUAGP511H2NR8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
55	RUAGP511H38E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
56	RUAGP511H3N8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
57	RUAGP511H3R8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
58	RUAGP511H3NR8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
59	RUAGP511H58E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
60	RUAGP511H5N8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
61	RUAGP511H5R8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
62	RUAGP511H5NR8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
63	RUAGP511H78E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
64	RUAGP511H7N8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
65	RUAGP511H7R8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
66	RUAGP511H7NR8E	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
67	RUAGP511FL8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
68	RUAGP511FLN8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
69	RUAGP511FLR8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
70	RUAGP511FLNR8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
71	RUAGP511F18E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
72	RUAGP511F1N8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
73	RUAGP511F28E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
74	RUAGP511F2N8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
75	RUAGP511F2R8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
76	RUAGP511F2NR8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
77	RUAGP511F38E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
78	RUAGP511F3N8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
79	RUAGP511F3R8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
80	RUAGP511F3NR8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
81	RUAGP511F58E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
82	RUAGP511F5N8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
83	RUAGP511F5R8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
84	RUAGP511F5NR8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
85	RUAGP511F78E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
86	RUAGP511F7N8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
87	RUAGP511F7R8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
88	RUAGP511F7NR8E	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800