

No	Model Name	(1)	(2)	(3)							(4)	(5)	(6)						(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)
		Rated heat output	Seasonal efficiency	Declared capacity for heating/Average climate							Bivalent temperature	Degradation coefficient	Declared coefficient of performance for heating/Average Climate						For air-to-water heat pumps: Operation limit temperature TOL	Heating water operating limit temperature	Electric power input				Capacity control	Sound power level	Rated air flow
		Prated	ηs	Pdh							Tbiv	Cdh	COPd						TOL	WTOL						Lwa	m³/h
				Tj=-7°C	Tj=2°C	Tj=7°C	Tj=12°C	Tj=biv	Tj=OL	Tj=-15			Tj=-7°C	Tj=2°C	Tj=7°C	Tj=12°C	Tj=biv	Tj=OL			off mode	standby mode	thermostat-off mode	crankcase heater mode			
kW	%	kW	kW	kW	kW	kW	kW	kW	°C									°C	°C	kW	kW	kW	kW		dBA		
89	RUAGP561HL8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
90	RUAGP561HLN8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
91	RUAGP561HLR8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
92	RUAGP561HLNR8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
93	RUAGP561H28TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
94	RUAGP561H2N8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
95	RUAGP561H38TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
96	RUAGP561H3N8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
97	RUAGP561H3R8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
98	RUAGP561H3NR8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
99	RUAGP561H58TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
100	RUAGP561H5N8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
101	RUAGP561H5R8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
102	RUAGP561H5NR8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
103	RUAGP561H78TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
104	RUAGP561H7N8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
105	RUAGP561H7R8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
106	RUAGP561H7NR8TR	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800