

Low Temperature Application - RUAGP511C(L/1/2/3/5/7)(N)(R)8E

No	Model Name	(1)	(2)	(3)				(4)	(5)				(6)	(7)	(8)		(9)	(10)	(11)	(12)	(13)
		Rated cooling capacity Prated	Seasonal efficiency ηs	Declared capacity for heating/Average climate Pdc				Degradation co-efficient Cc	Declared coefficient of performance for heating/Average Climate EERd				off mode Poff	standby mode Psb	Electric power input		crankcase heater mode Pck	Capacity control	Sound power level	Rated air flow	Refrigerant (R32) Global Warming Potential
				Tj=35°C	Tj=30°C	Tj=25°C	Tj=20°C		Tj=35°C	Tj=30°C	Tj=25°C	Tj=20°C			thermostat-off mode Pto	crankcase heater mode Pck					
kW	%	kW	kW	kW	kW					kW	kW	kW	kW								
23	RUAGP511CL8E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
24	RUAGP511CLN8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
25	RUAGP511CLR8E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
26	RUAGP511CLNR8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
27	RUAGP511C18E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
28	RUAGP511C1N8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
29	RUAGP511C28E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
30	RUAGP511C2N8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
31	RUAGP511C2R8E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
32	RUAGP511C2NR8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
33	RUAGP511C38E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
34	RUAGP511C3N8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
35	RUAGP511C3R8E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
36	RUAGP511C3NR8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
37	RUAGP511C58E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
38	RUAGP511C5N8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
39	RUAGP511C5R8E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
40	RUAGP511C5NR8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
41	RUAGP511C78E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
42	RUAGP511C7N8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
43	RUAGP511C7R8E	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
44	RUAGP511C7NR8E	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	