

Low Temperature Application - RUAGP511C(L/1/2/3/5/7)(N)(R)8TR

No	Model Name	(1)	(2)	(3)				(4)	(5)				(6)	(7)	(8)		(9)	(10)	(11)	(12)	(13)
		Rated cooling capacity Prated	Seasonal efficiency ηs	Declared capacity for heating/Average climate Pdc				Degradation co-efficient Cc	Declared coefficient of performance for heating/Average Climate EERd				off mode Poff kW	standby mode Psb kW	Electric power input		Capacity control	Sound power level dB(A)	Rated air flow m3/h	Refrigerant (R32) Global Warming Potential GWP	
		kW	%	Tj=35°C kW	Tj=30°C kW	Tj=25°C kW	Tj=20°C kW		Tj=35°C	Tj=30°C	Tj=25°C	Tj=20°C			thermostat-off mode Pto kW	crankcase heater mode Pck kW					
23	RUAGP511CL8TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
24	RUAGP511CLN8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
25	RUAGP511CLR8TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
26	RUAGP511CLNR8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
27	RUAGP511C18TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
28	RUAGP511C1N8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
29	RUAGP511C28TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
30	RUAGP511C2N8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
31	RUAGP511C2R8TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
32	RUAGP511C2NR8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
33	RUAGP511C38TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
34	RUAGP511C3N8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
35	RUAGP511C3R8TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
36	RUAGP511C3NR8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
37	RUAGP511C58TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
38	RUAGP511C5N8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
39	RUAGP511C5R8TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
40	RUAGP511C5NR8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
41	RUAGP511C78TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
42	RUAGP511C7N8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
43	RUAGP511C7R8TR	180	192.7	180	133	84.6	37.8	2.5	3.3	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	
44	RUAGP511C7NR8TR	180	199.8	180	133	84.6	37.8	2.5	5.0	4.4	5.8	7.2	0.329	-	1.207	0.489	Variable	87.4	73,800	675	