

Low Temperature Application - RUAGP561C(L/1/2/3/5/7)(N)(R)8TR

No	Model Name	(1)	(2)	(3)				(4)	(5)				(6)	(7)	(8)		(9)	(10)	(11)	(12)	(13)
		Rated cooling capacity Prated	Seasonal efficiency ηs	Declared capacity for heating/Average climate Pdc				Degradation co-efficient Cc	Declared coefficient of performance for heating/Average Climate EERd				off mode Poff	standby mode Psb	Electric power input		Capacity control	Sound power level	Rated air flow	Refrigerant (R32) Global Warming Potential	
				Tj=35°C	Tj=30°C	Tj=25°C	Tj=20°C		Tj=35°C	Tj=30°C	Tj=25°C	Tj=20°C			thermostat-off mode Pto	crankcase heater mode Pck					dB(A)
		kW	%	kW	kW	kW	kW					kW	kW	kW	kW						
45	RUAGP561CL8TR	200	192.4	200	148	94	42	2.5	3.1	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
46	RUAGP561CLN8TR	200	199.7	200	148	94	42	2.5	4.5	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
47	RUAGP561CLR8TR	200	192.4	200	148	94	42	2.5	3.1	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
48	RUAGP561CLNR8TR	200	199.7	200	148	94	42	2.5	4.5	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
49	RUAGP561C28TR	200	192.4	200	148	94	42	2.5	3.1	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
50	RUAGP561C2N8TR	200	199.7	200	148	94	42	2.5	4.5	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
51	RUAGP561C38TR	200	192.4	200	148	94	42	2.5	3.1	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
52	RUAGP561C3N8TR	200	199.7	200	148	94	42	2.5	4.5	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
53	RUAGP561C3R8TR	200	192.4	200	148	94	42	2.5	3.1	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
54	RUAGP561C3NR8TR	200	199.7	200	148	94	42	2.5	4.5	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
55	RUAGP561C58TR	200	192.4	200	148	94	42	2.5	3.1	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
56	RUAGP561C5N8TR	200	199.7	200	148	94	42	2.5	4.5	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
57	RUAGP561C5R8TR	200	192.4	200	148	94	42	2.5	3.1	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
58	RUAGP561C5NR8TR	200	199.7	200	148	94	42	2.5	4.5	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
59	RUAGP561C78TR	200	192.4	200	148	94	42	2.5	3.1	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
60	RUAGP561C7N8TR	200	199.7	200	148	94	42	2.5	4.5	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
61	RUAGP561C7R8TR	200	192.4	200	148	94	42	2.5	3.1	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	
62	RUAGP561C7NR8TR	200	199.7	200	148	94	42	2.5	4.5	4.2	5.8	7.4	0.329	-	1.207	0.489	Variable	90.9	73,800	675	